

Filling Capacities

Engine oil		HD oils to API classification SD or SE, viscosity: summer SAE 30, winter SAE 20, at continuous temperatures between - 15 ⁰ C and 0 ⁰ C SAE 20 W 20, or SAE 10 W for continuous temperatures below - 15 ⁰ C. (multi-grade oils: 15 W 50 or 20 W 50 when approved).
Engine oil change	1 tr/qt	Approx. 6.5/6.85 (level on dipstick is important)
Engine coolant	1 tr/qt	Approx. 16/17
Transmission oil		Hypoid oil SAE 90 to MIL-L 2105 B. API classification GL 5.
Transmission and differential	1 tr/qt	Approx. 3.8/4
Fuel tank	1 tr/gal.	Approx. 86/22,5, of which 11 liters 2,9 gal. for reserve
Brake fluid reservoir	1 tr/qt	Approx. 0.2/0.2
Windshield washer and headlight cleaner reservoir	1 tr/qt	Approx. 8/8,5 (water)
Cleaning solution reservoir	1 tr/qt	Approx. 0.6/0.6
Performance		(with 5-speed transmission)
Top speed	km/h / mph	above 230 / 144
Acceleration 0 - 100 km/h, 0 - 62 mph	s	6.8
1000 m from standing start	s	27.0
Power to weight	kg/kW / kg/HP	8.3 / 6.0
Hill Climbing		(with 5-speed transmission)
1st gear	%	71
2nd gear	%	41
3rd gear	%	28
4th gear	%	18
5th gear	%	11