Mobil 1 Engine Oils

Additional product information, including Product Data Sheets and this chart, is available at Mobiloil.com 10/17/2011

10/17/2011					1					1	1	
						API, ILSAC,			Ford			
		Nominal	Nominal			and Other			Service			
		Phosphorus	Zinc Level,		Recommended	Industry	ACEA	GM Service	Fill	MB	BMW	VW
Brand	Viscosity	Level, PPM	PPM	Product Description	Consumer Applications	Approvals***	Approvals	Fill Approval	Approval	Approval	Approval	Approval
				Boosted, advanced full synthetic								
				formula designed for today's								
Mobil 1				longer oil change intervals in								
Extended				Honda, Chryslers and newer	Vehicles that require 5W-		A1/B1-08					
Performance	5W-20	800	900	Toyotas	20	GF-5,SN	A1/B1-10		X			
İ				Boosted, advanced full synthetic								
				formula designed for today's			A1/B1-08,					
Mobil 1				longer oil change intervals in			A5/B5-08,					
Extended				many domestic, including GM,	Vehicles that require 5W-	GF-5,SN	A1/B1-10,					
Performance	5W-30	800	900	and imported vehicles.	30 or 10W-30.	Honda HTO-06	A5/B5-10	dexos1	X			
				,								
				Boosted, advanced full synthetic			A1/B1-08,					
Mobil 1				formula designed for today's			A5/B5-08,					
Extended				longer oil change intervals in	Vehicles that require 5W-		A1/B1-10,					
Performance	10W-30	800	900	many domestics and imports.	30 or 10W-30.	GF-5,SN	A5/B5-10					
renomance	1000-30	800	900	many domestics and imports.		GF-5,5IN	A3/B3-10					
					Most vehicles that							
	0W-20			Advanced full synthetic	specify 0W-20 (newer							
	Advanced			formulation designed for	Toyotas and Hondas),							
	Fuel			enhanced fuel economy and cold	5W-20 and certain		A1/B1-08,					
Mobil 1	Economy	650	750	weather performance.	hybrids.	GF-5,SN	A1/B1-10		Х			
	0W-30			Advanced full synthetic								
	Advanced			formulation designed for	Most vehicles that							
	Fuel			enhanced fuel economy and cold	specify 5W-30 or 10W-		A1/B1-10,					
Mobil 1	Economy	650	750	weather performance.	30.	GF-5,SN	A5/B5-10		X			
				Advanced full synthetic		Chrysler						
				formulation designed to meet the	Porsche A40.	MS10850,						
				requirements of many European	Many European vehicles.	Nissan GT-R	A3/B3-08,			229.3/		502.00 /
Mobil 1	0W-40	1000	1100	vehicles.	HT/HS applications.	SN,SM,SL,SJ	A3/B4-08			229.5	Longlife 01	505.00
				Advanced full synthetic							_	
				formulation designed to meet the								
				requirements of many newer								
				vehicles including Hondas,								
				Fords, Chryslers and newer	Vehicles that require 5W-		A1/B1-08,					
Mobil 1	5W-20	800	900	Toyotas.	20.	GF-5,SN	A1/B1-10,		Χ			
WOODII 1	OW 20	000	000	Advanced full synthetic	20.	01 0,011	7(1/2) 10,					
				formulation designed to meet the			A1/D1 00					
				_			A1/B1-08, A5/B5-08,					
				requirements of many domestic,	Vehicles that require 5W-	GF-5,SN	A3/B3-06, A1/B1-10,					
Mobil 1	5W-30	000	000	including GM, and imported vehicles.	30. Corvette approved.	Honda HTO-06		dovoo1	Х			
IVIODII I	300-30	800	900		30. Corvette approved.	Horida HTO-06	A5/B5-10	dexos1	^			
				Higher viscosity, advanced full			10/50 00			000.4		504.04
	5147.50			synthetic formula designed for	Porsche.	011/014	A3/B3-08,			229.1		501.01,
Mobil 1	5W-50	1000	1100	performance vehicles	HT/HS applications.	SN/SM	A3/B4-08			/229.3		505.00
							A1/B1-08,					
				Advanced full synthetic formula			A5/B5-08,					
				designed for domestics and	Vehicles that require 5W-		A1/B1-10,					
Mobil 1	10W-30	800	900	imports	30 or 10W-30.	GF-5,SN	A5/B5-10					\
				Boosted, higher viscosity,								
				advanced full synthetic formula	HT/HS applications.		A3/B3-08,					1
				designed for performance	Racing and Flat tappet		A3/B4-08,					
Mobil 1	15W-50	1200	1300	vehicles.	applications.	SN/SM	A3/B3-10					
		. 200	. 300		11							
				Advanced full synthetic formula	Most diesel applications.	CJ-4, CI-4,						1
Mobil 1 Turbo				designed for diesel powered pick-	including engines with	CI-4 Plus, SM,						1
Diesel Truck	5W-40	1100	1200	ups and trucks.	diesel particulate filters.	SL	E7					1
DIOGOI TIUOK	JVV 70	1100	1200	apo ana truoko.	aloool particulate filters.	0.						

						API, ILSAC,			Ford			
		Nominal	Nominal			and Other			Service			
		Phosphorus	Zinc Level,		Recommended	Industry	ACEA	GM Service	Fill	MB .	BMW	. vw
Brand	Viscosity	Level, PPM	PPM	Product Description	Consumer Applications	Approvals***	Approvals	Fill Approval	Approval	Approval	Approval	Approval
							A1/B1-08,					
				Boosted, advanced full synthetic			A5/B5-10,					
Mobil 1 High	51A/ 00	4000	4400	formula designed for higher	Vehicles that require 5W-	01./0.1	A1/B1-10,					
Mileage	5W-30	1000	1100	mileage vehicles.	30 or 10W-30.	SL/SJ	A5/B5-10					
				Boosted, advanced full synthetic			A3/B3-08,					
Mobil 1 High				formula designed for higher	Vehicles that require 5W-	01.70.1	A3/B4-08,					
Mileage	10W-30	1000	1100	mileage vehicles.	30 or 10W-30.	SL/SJ	A3/B3-10					
				Boosted, advanced full synthetic			A3/B3-08,					
Mobil 1 High				formula designed for higher	Higher viscosity	011/01/101/01	A3/B4-08,					
Mileage	10W-40	1000	1100	mileage vehicles.	applications.	SN/SM/SL/SJ	A3/B3-10					
				Advanced full synthetic formulas								
				designed specifically for	Low SAPS.							
Mobil 1 ESP				passenger car diesels that have	Available at most MB					229.31,		
Formula M	5W-40	800	900	particulate filters.	dealers.	None				229.51		
				Advanced full synthetic formulas								
				designed specifically for	Low SAPS.	Porsche C30.						
Mobil 1 ESP				passenger car diesels that have	Available at many	Chrysler MS-				229.31,		
Formula	5W-30	800	900	particulate filters.	Chrysler dealers.	11106	C3-08, C2-08			229.51	Longlife-04	504/507
				Advanced full synthetic formulas								
				designed specifically for		SN/SM/SJ/SH,						
Mobil 1 Racing				motorcycles where clutch	All motorcycles where	JASO MA1						
4T	10W-40	1200	1300	lubrication is also important.	10W-40 is specified	2006						
				Advanced full synthetic formulas	All motorcycles where							
				designed specifically for	20W-50 is specified,							
				motorcycles where clutch	especially V-Twin							
Mobil 1 V-Twin	20W-50	1600	1700	lubrication is also important.	engines	SJ						
				Advanced full synthetic formula								
				specifically designed to maximize	Race engines. Not							
				horsepower under race	recommended for street							
Mobil 1 Racing	0W-30	1750	1850	conditions.	use.							
_				Advanced full synthetic formula								
				specifically designed to maximize	Race engines. Not							
				engine protection under race	recommended for street							
Mobil 1 Racing	0W-50	1750	1850	conditions.	use.							

^{**} API SH and API SG are no longer licensable.

^{***}For a full list of industry and original equipment manufacturer approvals by product and viscosity, see the Product Data Sheets which are available online at www.mobiloil.com.