

Maintenance Checklist – 911 Carrera/S/4/4S (991) (2012-on)

Required Maintenance and Lubrication Service

* Oil Change Every 10,000 miles (15,000 km) or 1 year. See Below Check Box.
 Maintenance (Labor Operation 03 16 00) See Technical Manual After 40,000, 80,000, 120,000, 160,000 miles etc. / 60,000, 120,000, 180,000, 240,000 km etc. Note: If the mileage for scheduled maintenance is not reached, maintenance must be performed no later than after 4, 8, 12 years.
The terms 'check' and 'inspection' include all necessary subsequent work such as adjusting, readjusting, correcting and topping off, but do not include repairing, replacing and reconditioning parts or assemblies.
Electrics
Diagnosis system: Read out fault memory; reset maintenance interval
Uindshield wiper/washer system, headlight washer: Check function and nozzle adjustment
Horn: Check operation
Tires: Check tire pressure (TPM)
Batteries and ventilation hoses: Check condition
Electrical equipment as well as indicator and warning lights: Check operation
Inside of Vehicle
Pollen filter: Replace filter element
Seat belts: check function and condition
Door locks: check function
Front Luggage Compartment
Pollen filter: Replace pre-filter element
Check front lid lock and safety hook of the front lid for secure seating and function properly
Uindshield wiper/washer system, headlight washer: Check fluid level and antifreeze protection level
Check firewall body drains for debris
Outside of Vehicle
Check wiper blades
Uehicle lighting: Check operation
All headlights: Check adjustment
Radiators and air intakes: Visual inspection for exterior debris and blockage
Under the Vehicle
🖵 Drain engine oil
Vehicle underside and engine compartment: Visual inspection for leaks (oils and fluids) and abrasion (lines and hoses); Underbody panels: visual inspection for completeness, secure installation and damage
Tires: Check condition
Brake system: Visual inspection of the brake pads and brake discs for signs of wear (without removing wheels)
Brake hoses and lines: Visual inspection for damage, correct routing and corrosion Check brake fluid level
Steering gear: Visual inspection of the dust boots for damage
Tie rod ends: Check play and dust boots
Axle shafts/Drive shafts: Visual inspection of the dust boots for leaks & signs of damage/wear
Exhaust system: Visual inspection for leaks and damage; check mounting and heat shields
Engine Compartment
Air filter: Replace filter elements
Change oil filter and fill engine oil (Every 10,000 miles/15,000 km, see separate Oil Change Sheet, PNA 000 162 LC)
Fuel lines and connections: Visual inspection for damage and leaks
Usual inspection for leaks (oils and fluids)
Coolant: Check level and antifreeze protection level
PDCC: Check fluid level
Check firewall body drains for debris
Additional Maintenance – Replace Spark Plugs (Labor Operation 03 81 00)

Replace spark plugs: every 40,000 miles / 60,000 km or 4 years

Additional Maintenance - Drive Belt Labor operation 03 60 00 ...

- Check drive belt at 40,000 miles (60,000 km) or every 4 years
- $\hfill\square$ Check drive belt at 100,000 miles (150,000 km) or every 10 years
- Check drive belt at 160,000 miles (240,000 km) or every 16 years

Additional Maintenance every 60,000 miles / 90,000 km or 6 years (Labor Operation 03 83 00 ..)

Replace PDCC reservoir

Replace drive belt

□ Change all-wheel drive controller oil – 911 Carrera 4 – 4-wheel drive models

Additional Maintenance every 80,000 miles / 120,000 km or 4 years (Labor Operation 03 85 00 ...) Ancillary unit mounts and chassis: visual inspection of all rubber mountings and boots for damage

Additional Maintenance every 120,000 miles / 180,000 km or 12 years (Labor Operation 03 88 00 ...)

□ Manual transmission: change oil

PDK transmission: change oil

PDK transmission: change clutch oil

□ Change front differential oil – 911 Carrera 4 – 4-wheel drive models only

Additional Maintenance every 2 years (Labor Operation 03 51 00 ..)

Change brake fluid (use only Original Porsche Brake Fluid)

Tire sealant (For MY 2014-on, check expiration date and replace as necessary, for MY 2012-13 see below)

Additional Maintenance every 4 years (Labor Operation 03 52 00 ..)

Replace tire sealant (For MY 2012-13 the replacement interval is "every 4 years", for MY 2014-on see above)

Inspection Performed - Technician Signature:

Road Test Check

- Remote control, front seats, foot brake and electric parking brake (also operating travel), engine, clutch, steering, transmission, ParkAssist, cruise control, PSM, PASM & Sport switches, sports exhaust system, door mirror fold-in function, heater, air-conditioning system and instruments: Check operation
- Oils, fluids: Visual inspection for leaks

Road Test Performed - Technician Signature:

Customer Name:	Date://
VIN: WPO	
Mileage (check one) 🖵 Miles 🖵 Kilometers:	
Dealer Name:	Dealer Code:
Repair Order #:	
Technician Name:	
Technician Signature:	