

Maintenance Checklist - 911 Carrera/S/4/4S/Turbo/S (991) (2014-on)

Required Maintenance and Lubrication Service

* Oil Change Every 10,000 miles (15,000 km) or 1 year. See Below Check Box.
Maintenance (Labor Operation 03 16 00) See Technical Manual After 40,000, 80,000, 120,000, 160,000 miles etc. / 60,000, 120,000, 180,000, 240,000 km etc. Note: If the mileage for scheduled maintenance is not reached, maintenance must be performed no later than after 4, 8, 12 years.
The terms 'check' and 'inspection' include all necessary subsequent work such as adjusting, readjusting, correcting and topping off, but do not include repairing, replacing and reconditioning parts or assemblies.
Electrics
☐ Diagnosis system: Read out fault memory; reset maintenance interval
☐ Windshield wiper/washer system, headlight washer: Check function and nozzle adjustment
☐ Horn: Check operation
☐ Tires: Check tire pressure (TPM)
☐ Batteries and ventilation hoses: Check condition
☐ Electrical equipment as well as indicator and warning lights: Check operation
☐ Check actuator travel of brake shoes (911 Turbo/Turbo S only)
Inside of Vehicle
Pollen filter: Replace filter element
■ Seat belts: check function and condition
☐ Door locks: check function
Front Luggage Compartment
Pollen filter: Replace pre-filter element
☐ Check front lid lock and safety hook of the front lid for secure seating and function properly
☐ Windshield wiper/washer system, headlight washer: Check fluid level and antifreeze protection level
☐ Check firewall body drains for debris
Outside of Vehicle
☐ Check wiper blades
☐ Vehicle lighting: Check operation
☐ All headlights: Check adjustment
Radiators and air intakes: Visual inspection for exterior debris and blockage
☐ Check the two Targa center bar drains for debris (911 Targa models only)
Under the Vehicle
☐ Drain engine oil
☐ Vehicle underside and engine compartment: Visual inspection for leaks (oils and fluids) and abrasion (lines and hoses); Underbody panels: visual inspection for completeness, secure installation and damage
Tires: Check condition
Brake system: Visual inspection of the brake pads & brake discs for wear (w/o removing wheels) (Except PCCB)
☐ Vehicles with PCCB: As of MY 2014, PCCB Brake discs must be checked for wear during every service and whenever
brakes pads are replaced using special tool VAS 6813. Please refer to workshop manual for work procedure. Brake hoses and lines: Visual inspection for damage, correct routing and corrosion Check brake fluid level
☐ Steering gear: Visual inspection of the dust boots for damage Tie rod ends: Check play and dust boots
Rear axle steering: Check bellows, dust boots and play on joints
Axle shafts/Drive shafts: Visual inspection of the dust boots for leaks & signs of damage/wear
■ Exhaust system: Visual inspection for leaks and damage; check mounting and heat shields
Engine Compartment
☐ Air filter: Replace filter elements
☐ Change oil filter and fill engine oil (Every 10,000 miles/15,000 km, see separate 0il Change Sheet, PNA 000 162 LC)
☐ Fuel lines and connections: Visual inspection for damage and leaks
☐ Visual inspection for leaks (oils and fluids)
☐ Coolant: Check level and antifreeze protection level
PDCC: Check fluid level
☐ Check firewall body drains for debris

Additional Maintenance - Replace Spark Plugs (Labor Operation (03 81 00)	
Replace spark plugs: every 40,000 miles / 60,000 km or 4 years (Except Turbo/S)		
Replace spark plugs: 911 Turbo/Turbo S every 30,000 miles / 45,00	JO km or 4 years	
Additional Maintenance - Drive Belt Labor operation 03 60 00		
Check drive belt at 40,000 miles (60,000 km) or every 4 years		
☐ Check drive belt at 100,000 miles (150,000 km) or every 10 years ☐ Check drive belt at 160,000 miles (240,000 km) or every 16 years		
	00.)	
Additional Maintenance – Convertible Top (Labor Operation 03 70		
Service and maintain convertible top: every 20,000 miles / 30,000 k		
Additional Maintenance – Targa Roof (Labor Operation 03 71 00)		
☐ Service and maintain Targa roof: every 20,000 miles / 30,000 km or	2 years	
Additional Maintenance every $60,000 \text{ miles} / 90,000 \text{ km or } 6 \text{ y}$	rears (Labor Operation 03 83 00)	
Replace PDCC reservoir		
Replace drive belt Change all-wheel drive controller oil (4-wheel drive models only)		
Additional Maintenance every 80,000 miles / 120,000 km or 4	NORMO (Labor Operation 02.95.00.)	
Ancillary unit mounts and chassis: visual inspection of all rubber mounts	•	
Additional Maintenance every 120,000 miles / 180,000 km or	12 years (Labor Operation 03 88 00)	
☐ Manual transmission: change oil		
PDK transmission: change oil		
□ PDK transmission: change clutch oil □ All-wheel final drive: change oil (4-wheel drive models only)		
Additional Maintenance every 2 years (Labor Operation 03 51 00)		
 ☐ Change brake fluid (use only Original Porsche Brake Fluid) ☐ Tire sealant (check expiration date and replace as necessary) 		
Inspection Performed - Technician Signature:		
		
Road Test Check ☐ Remote control, front seats, foot brake and electric parking brake (also	o operating travel) engine clutch steering	
transmission, ParkAssist, cruise control, PSM, PASM & Sport switches		
tion, heater, air-conditioning system and instruments: Check operation		
Oils, fluids: Visual inspection for leaks		
Road Test Performed - Technician Signature:		
Customer Name:	Date:/	
VIN: WPO		
Mileage (check one) Miles Kilometers:		
Dealer Name:	Dealer Code:	
Repair Order #:		
Technician Name:		
Technician Signature:		