

**WM 465004 MEASURING FRONT BRAKE DISCS (EXCEPT CARRERA "EDITION", CARRERA CABRIOLET "EDITION", CARRERA 4 "EDITION", CARRERA 4 CABRIOLET "EDITION") > SUBSEQUENT WORK**

1. Fit the front wheels. → Installing Wheel

**WM 465019 REMOVING AND INSTALLING FRONT BRAKE DISC (EXCEPT CARRERA "EDITION", CARRERA CABRIOLET "EDITION", TURBO S, CARRERA 4 "EDITION", TURBO S CABRIO, CARRERA 4 CABRIOLET "EDITION") > TECHNICAL VALUES**

Location	Description	Type	Basic value	Tolerance 1	Tolerance 2
Brake calliper to wheel carrier, front and rear axle	M10/always use new nuts on front and rear axle following removal.	Tightening torque	65 Nm (48 ftlb.)		
Brake disc to wheel hub	M6 screw	Tightening torque	10 Nm (7.5 ftlb.)		
Wheel driver pin to wheel hub (central bolt on 911 Turbo/GTS)	Cheese head bolts, M6 x 30/always use new bolts following removal	Tightening torque	14 Nm (10.5 ftlb.)		
Wheel driver pin to wheel hub (central bolt on 911 GT3)	Cheese head bolts, M8 x 32/always use new screws following removal	Tightening torque	31 Nm (23 ftlb.)		

**WM 465019 REMOVING AND INSTALLING FRONT BRAKE DISC (EXCEPT CARRERA "EDITION", CARRERA CABRIOLET "EDITION", TURBO S, CARRERA 4 "EDITION", TURBO S CABRIO, CARRERA 4 CABRIOLET "EDITION") > PRELIMINARY WORK**

1. Raise the vehicle.
  - 4X00IN LIFTING THE VEHICLE .
2. Remove wheel.
  - 440519 REMOVING AND INSTALLING WHEEL .
  - 440519 REMOVING AND INSTALLING WHEEL WITH CENTRAL BOLT .

**WM 465019 REMOVING AND INSTALLING FRONT BRAKE DISC (EXCEPT CARRERA "EDITION", CARRERA CABRIOLET "EDITION", TURBO S, CARRERA 4 "EDITION", TURBO S CABRIO, CARRERA 4 CABRIOLET "EDITION") > REMOVING AND INSTALLING FRONT BRAKE DISC > REMOVING FRONT BRAKE DISC**