

**Running gear**

**Front axle**

Spring wire dia. (sport-type)	mm/in	10.9(8...11.6)/0.43(0.31/0.46)
Spring coil dia. (sport-type)	mm/in	103/4.06
Number of coils		6.75(9)
Stabilizer dia. (sport-type)	mm/in	21(22)/0.83(0.87)
Spring wire dia. (sport-type)	mm/in	11.2(11.6)/0.44(0.46)
Spring coil dia. (sport-type)	mm/in	103/4.06
Number of coils		7.0
Stabilizer dia. (sport-type)	mm/in	20(22)/0.79(0.87)

**Rear axle**

Spring wire dia. (sport-type)	mm/in	13(13.5)/0.51(0.53)
Spring coil dia. (sport-type)	mm/in	102(102)/4.02(4.02)
Number of coils		8(7.25)
Stabilizer dia. (sport-type)	mm/in	18(20)/0.71(0.79)
Spring wire dia. (sport-type)	mm/in	13(13.9)/0.51(0.55)
Spring coil dia. (sport-type)	mm/in	102(101)/4.02(3.98)
Number of coils		8.3(8.0)
Stabilizer dia. (sport-type)	mm/in	17(20)/0.67(0.79)

<b>ROW Carrera</b>	11.9(8...11.6)	103	6.45(9)	21(22)
<b>ROW Carrera S</b>	11.9(8...11.6)	103	6.45(9)	21(22)
<b>USA Carrera</b>	11.2(11.6)/0.44(0.46)	103/4.06	7.0	20(22)/0.79(0.87)
<b>USA Carrera S</b>	11.2(11.6)/0.44(0.46)	103/4.06	7.0	20(22)/0.79(0.87)
<b>RdW Carrera</b>	16.48:1(16.60:1)	2.47 (2.49)	11.74/38.52	
<b>RdW Carrera S</b>	16.48:1(16.60:1)	2.47 (2.49)	11.74/38.52	

<b>RdW Carrera</b>	17(18)	=	=	=	=	7.5(7.25)
<b>USA Carrera S</b>	17(18)	=	=	=	=	7.5(7.25)