

993 Suspension Specs(factory)	RoW std	All US includes M030	RoW M030 & CS/C4S	RS M002/M003		964 Suspension Specs	RoW std	RoW RS
Front	154+/-10	174+/-10	144+/-10	124+/-10		175+/-10	165+/-10	125+/-5
rear	147+/-10	157+/-10	127+/-10	107+/-10		268+/-10	258+/-10	223+/-5
max l/r diff 5mm						+25+/-5	+25+/-5	+25+/-5
Toe(front)mm	+5+/-5'	+5+/-5'	+5+/-5'	+5+/-5'		+25+/-5	+25+/-5	+25+/-5
Toe(rear)mm	+10+/-5'	+10+/-5'	+10+/-5'	+10+/-5'		+10+/-5	+10+/-5	+15+/-5'
camber(front)	-20+/-10	-20+/-10	-20+/-10	-1*27+/-30'		0*+/-10'	0*+/-10'	-1*+/-10
camber(rear)	-1*10+/-15'	-1*10+/-15'	-1*10+/-15'	-1*20+/-10'		-40+/-5'	-40+/-5'	-1*+/-10'
caster	5*20+15'-30'	5*20+15'-30'	5*20+15'-30'	5*20+15'-30'		4*25+15'-30'	4*25+15'-30'	4*25+15'-30'