Mobil 1 Engine Oils

Additional product information, including Product Data Sheets and this chart, is available at Mobiloil.com 10/17/2011

10/17/2011												
		Nominal Phosphorus	Nominal Zinc Level,		Baranan da d	API, ILSAC, and Other	ACEA	GM Service	Ford Service Fill	МВ	вмм	vw
Brand	Viscosity	Level, PPM	PPM	Product Description	Recommended Consumer Applications	Industry Approvals***	Approvals	Fill Approval	Approval	Approval	Approval	Approval
				Boosted, advanced full synthetic	P		търготино	· 				
				formula designed for today's								
Mobil 1				longer oil change intervals in								
Extended				Honda, Chryslers and newer	Vehicles that require 5W-		A1/B1-08					
Performance	5W-20	800	900	Toyotas	20	GF-5,SN	A1/B1-10		X			
				Boosted, advanced full synthetic								
				formula designed for today's			A1/B1-08,					
Mobil 1				longer oil change intervals in			A5/B5-08,					
Extended	514/ 00			many domestic, including GM,	Vehicles that require 5W-	GF-5,SN	A1/B1-10,					
Performance	5W-30	800	900	and imported vehicles.	30 or 10W-30.	Honda HTO-06	A5/B5-10	dexos1	Х			
				Deserted adversed full south offer			A4/D4 00					
Mobil 1				Boosted, advanced full synthetic formula designed for today's			A1/B1-08, A5/B5-08,					
Extended				longer oil change intervals in	Vehicles that require 5W-		A3/B3-06, A1/B1-10,					
Performance	10W-30	800	900	many domestics and imports.	30 or 10W-30.	GF-5,SN	A5/B5-10					
Performance	10W-30	800	900	many domestics and imports.	Most vehicles that	O1 -5,51 1	A3/B3-10					
	0W-20			Advanced full synthetic	specify 0W-20 (newer							
	Advanced			formulation designed for	Toyotas and Hondas),							
	Fuel			enhanced fuel economy and cold	5W-20 and certain		A1/B1-08,					
Mobil 1	Economy	650	750	weather performance.	hybrids.	GF-5,SN	A1/B1-10		Χ			
	0W-30			Advanced full synthetic	,	,-						
	Advanced			formulation designed for	Most vehicles that							
	Fuel			enhanced fuel economy and cold	specify 5W-30 or 10W-		A1/B1-10,					
Mobil 1	Economy	650	750	weather performance.	30.	GF-5,SN	A5/B5-10		X			
				Advanced full synthetic		Chrysler						
				formulation designed to meet the	Porsche A40.	MS10850,						
				requirements of many European	Many European vehicles.	Nissan GT-R	A3/B3-08,			229.3/		502.00 /
Mobil 1	0W-40	1000	1100	vehicles.	HT/HS applications.	SN,SM,SL,SJ	A3/B4-08			229.5	Longlife 01	505.00
				Advanced full synthetic								
				formulation designed to meet the								
				requirements of many newer								
				vehicles including Hondas, Fords, Chryslers and newer	Vehicles that require 5W-		A1/B1-08,					
Mobil 1	5W-20	800	900	Toyotas.	20.	GF-5,SN	A1/B1-00, A1/B1-10,		Х			
I IIddivi	011 20	000	000	Advanced full synthetic	20.	01 0,011	71751 10,		Α			
				formulation designed to meet the			A1/B1-08,					
				requirements of many domestic,			A5/B5-08,					
				including GM, and imported	Vehicles that require 5W-	GF-5,SN	A1/B1-10,					
Mobil 1	5W-30	800	900	vehicles.	30. Corvette approved.	Honda HTO-06	A5/B5-10	dexos1	X			
				Higher viscosity, advanced full								
				synthetic formula designed for	Porsche.		A3/B3-08,			229.1		501.01,
Mobil 1	5W-50	1000	1100	performance vehicles	HT/HS applications.	SN/SM	A3/B4-08			/229.3		505.00
							A1/B1-08,					
				Advanced full synthetic formula			A5/B5-08,					
				designed for domestics and	Vehicles that require 5W-		A1/B1-10,					
Mobil 1	10W-30	800	900	imports	30 or 10W-30.	GF-5,SN	A5/B5-10					\
	1			Boosted, higher viscosity,	IT I I I I I I I I I		40/50 00				1	
	1			advanced full synthetic formula	HT/HS applications.		A3/B3-08,				1	
Mahild	4514/50	4000	4000	designed for performance	Racing and Flat tappet	CNI/CNA	A3/B4-08,					
Mobil 1	15W-50	1200	1300	vehicles.	applications.	SN/SM	A3/B3-10	1			 	
	1			Advanced full synthetic formula	Most diesel applications.	CJ-4, CI-4,					1	
Mobil 1 Turbo	1			designed for diesel powered pick-	including engines with	CI-4 Plus, SM,					1	
Diesel Truck	5W-40	1100	1200	ups and trucks.	diesel particulate filters.	SL	E7				1	
	5.7 10	1.700	1200	1-1- 3.10 1.00.10.	and particulate interes.	, ,		Į				

		Nominal	Nominal			API, ILSAC, and Other			Ford Service			
		Phosphorus	Zinc Level,		Recommended	Industry	ACEA	GM Service	Fill	MB	BMW	vw
Brand	Viscosity	Level, PPM	PPM	Product Description	Consumer Applications	Approvals***	Approvals	Fill Approval	Approval	Approval	Approval	Approval
							A1/B1-08,					
				Boosted, advanced full synthetic			A5/B5-10,					
Mobil 1 High	5W-30	4000	1100	formula designed for higher	Vehicles that require 5W- 30 or 10W-30.	SL/SJ	A1/B1-10,					
Mileage	500-30	1000	1100	mileage vehicles. Boosted, advanced full synthetic	30 OF 10VV-30.	2D/20	A5/B5-10 A3/B3-08,					
Mobil 1 High				formula designed for higher	Vehicles that require 5W-		A3/B3-08, A3/B4-08,					
Mileage	10W-30	1000	1100	mileage vehicles.	30 or 10W-30.	SL/SJ	A3/B4-06, A3/B3-10					
Mileage	1000-30	1000	1100	Boosted, advanced full synthetic	30 01 10VV-30.	32/33	A3/B3-10					
Mobil 1 High				formula designed for higher	Higher viscosity		A3/B3-08, A3/B4-08,					
Mileage	10W-40	1000	1100	mileage vehicles.	applications.	SN/SM/SL/SJ	A3/B3-10					
·····oago		1000	1100	I I I I I I I I I I I I I I I I I I I	аррисанопог	0.1,0.1.,02.00	7.0720 10					
				Advanced full synthetic formulas								
				designed specifically for	Low SAPS.							
Mobil 1 ESP				passenger car diesels that have	Available at most MB					229.31.		
Formula M	5W-40	800	900	particulate filters.	dealers.	None				229.51		
				Advanced full synthetic formulas								
				designed specifically for	Low SAPS.	Porsche C30.						
Mobil 1 ESP				passenger car diesels that have	Available at many	Chrysler MS-				229.31,		
Formula	5W-30	800	900	particulate filters.	Chrysler dealers.	11106	C3-08, C2-08			229.51	Longlife-04	504/507
				Advanced full synthetic formulas								ļ
				designed specifically for		SN/SM/SJ/SH,						
Mobil 1 Racing				motorcycles where clutch	All motorcycles where	JASO MA1						
<mark>4T</mark>)	10W-40	1200	<mark>1300</mark>	lubrication is also important.	10W-40 is specified	2006						
				Advanced full synthetic formulas	All motorcycles where							
				designed specifically for	20W-50 is specified,							
	00144 50	4000	4700	motorcycles where clutch	especially V-Twin	0.1						
Mobil 1 V-Twin	20W-50	<mark>1600</mark>	<mark>1700</mark>	lubrication is also important.	engines	SJ	1					\vdash
				Advanced full synthetic formula	Dans engines Net							1
				specifically designed to maximize horsepower under race	recommended for street							[
Mobil 1 Racing	0W-30	1750	1850	conditions.	use.							1
IVIODII I Racing	000-30	1750	1000	Advanced full synthetic formula	use.							
				specifically designed to maximize	Page engines Not]
				engine protection under race	recommended for street]
Mobil 1 Racing	0W-50	1750	1850	conditions.	use.							1
WOULD I NACING	044-90	1730	1000	conditions.	uoc.	l						

^{**} API SH and API SG are no longer licensable.

***For a full list of industry and original equipment manufacturer approvals by product and viscosity, see the Product Data Sheets which are available online at www.mobiloil.com.