

Maintenance Schedule - 911 Carrera (993), 911 Carrera (993) Turbo

Required Maintenance and Lubrication Service

Recommended service interval		r vehicles that accumu	ılate low yearly mileage between requi	red
☐ Diagnosis syst☐ Parking brake:☐ Brake system:☐ Brake fluid: Ch☐ Steering gear:☐ Tie rods: Chec☐ Ball joints: Vis☐ Drive shafts: V☐ Exhaust syste☐ Tires and spar☐ Seals for door☐ Vehicle lights:☐ Windshield wawinter season☐ Battery: Chec☐	Visual inspection for leaks em: Read out fault memory Check free travel of parking-Visual inspection of brake pareck level Visual inspection of the bellow k play and dust boots ual inspection of dust boots for its visual inspection of boots for In: Visual inspection for leaks e wheel: Check condition and so, hood and roof: Remove rub Check operation and headlight	ds and brake discs to che ws for damage or damage eaks and damage and damage; check tightr correct tire pressure ober residue from body se at alignment a fluid level, nozzle aim an cration eter test	ness eal contact areas, apply suitable lubricant nd washer fluid anti-freeze protection level fo	r the
Required maint	enance and lubrication se	rvice every 15 000 mil	iles / 24 000 km	
☐ Diagnosis sys: ☐ Anti-pollen filte ☐ Oils and fluids ☐ Air filter: Chec ☐ Crankcase vei ☐ Fuel system: \(\) ☐ Intake air: Che ☐ Parking brake ☐ Brake hoses a ☐ Brake fluid: Cl ☐ Brake system ☐ Clutch: Check ☐ Throttle linkag ☐ Resonance fla ☐ Steering gear ☐ Tie rods: Chec ☐ Power-assiste ☐ Ball joints: Vis ☐ Manual transm ☐ Automatic tran ☐ Drive shafts: \(\) ☐ Exhaust syste ☐ Tires and spa ☐ Door locks, h	Visual inspection of brake par play or final position of clutch e: Check for smooth movement p and Varioram: Check opera Visual inspection of the bello ck play and dust boots disteering/clutch: Check fluid ual inspection of dust boots for hission/axle drives: Check oil hismission: Check, fluid level Visual inspection of boots for m: Visual inspection for leaks are wheel: Check condition and Lubricate	clearance and tightness ons for tightness brake lever clearance, damage and cads and brake discs to change and full throttle opening tion (Carrera only) ows for damage levels or damage, check tightne level leaks and damage and damage, check tight decorrect tire pressure	corrosion neck for wear ng ess of wheel alignment adjustment/mounting	bolts

[©] Porsche Cars North America, Inc., Porsche Publications – Edition 2/00

Required maintenance and lubrication service every 15 000 miles / 24 000 km (cont'd)
□ Seals for doors, hood and roof: Remove rubber residue from body seal contact areas, apply suitable lubricant □ Vehicle lights: Check operation □ All headlights: Check Alignment □ Horn: Check operation
Windshield washer, headlight washer: Check fluid level, nozzle aim and washer fluid freeze protection level and check wiper system operation
Check operation: All electrical equipment, indicator and warning lights
During road or dynamometer test:
 □ Brake pedal, parking brake, clutch, automatic speed control, steering, heating, air conditioning and instruments: ○ Operations test □ Oils and fluids: Visual inspection for leaks
Additional service every 30 000 miles / 48 000 km
 □ V-Belt and Polyrib belt: Check condition and tension □ Replace sparks plugs □ Air filter: Replace filter element □ Replace both engine oil filters □ Automatic transmission: Change ATF and ATF-filter □ Drive belt for power steering pump: Check condition
Additional service every 60 000 miles / 96 000 km
 ■ Manual transmission and axle drives: Change oil ■ Automatic transmission: Change oil in differential ■ Fuel filter: Replace
Service every 3 years
☐ Brake system: Change brake fluid (only use Genuine Porsche Brake Fluid)
Service after 4, 8, 10 and then every 2 years
☐ Air bag supplemental restraint system scheduled maintenance
Scheduled maintenance points
The service intervals apply under normal driving conditions. If you drive in dusty areas, check air filter more often and replace if necessary. The conditions of oil and wear-and-tear items (such as tires, brakes, clutch lining) depend greatly upon the amount of driving and on driving habits. Therefore, oil and wear-and-tear-items should be checked more frequently, and if necessary, replaced at shorter intervals. Checking for exterior damage and the protective undercoating is also recommended. A service should be performed at least once a year, preferably before the winter months (see Recommended Yearly Service).
The terms "inspect" and "check" include all associated work such as checking the condition, adjustments, readjustments, corrections and replenishment. They do not include the repair, replacement or overhaul of components of assemblies.
The maintenance points stated above are valid for all vehicle types of the model line in question.
Customer Name: VIN:
Dealer Name: Dealer Code:
Date: Mileage/Kilometers: Repair Order #:
Technician Name:Technician Signature: