

<b>STOCK CONFIGURATION</b>				
<b>Engine speed</b>	<b>Intake-air temperature</b>	<b>Ambient temperature</b>	<b>Mass air flow (MAF)</b>	<b>Vehicle speed</b>
3348.5	21	13.5	83.2	105.01
3411.5	21	13.5	57.9	104.9
3398	21	13.5	56.4	104.82
3382.25	21	13.5	57.5	104.85
3398.5	21	13.5	58.9	104.75
3391	21	13.5	59.1	104.72
3377.75	21	13.5	59.7	104.7
3383.75	21	13.5	69.4	104.54
3377.25	21	13.5	68.8	104.48
3374.25	21	13.5	68.4	104.33
3364.25	21	13.5	68.2	104.2
3351.5	21	13.5	67.6	103.87

<b>DO88 TURBO INTERCOOLER KIT</b>				
<b>Engine speed</b>	<b>Intake-air temperature</b>	<b>Ambient temperature</b>	<b>Mass air flow (MAF)</b>	<b>Vehicle speed</b>
3104.25	16	12.8	97.4	115.92
3090.5	16	12.8	96.7	115.73
3096.25	16	12.8	98.5	115.65
3088.5	16	12.8	111.8	115.51
3089.25	16	12.8	111.2	115.38
3078	16	12.8	109.8	115.31
3082.5	16	12.8	138.8	115.06
3089.25	16	12.8	180.7	115.07
3086.25	16	12.8	238.3	115.12
3088.5	16	12.8	288.3	115.31
3128.75	16	12.8	320.4	116.12