

Engine	2.5	2.7 00-02	2.7 02-04
Type	Six cylinder, horizontally opposed, water-cooled		
Bore	3.4 in. (85.5 mm)		
Stroke	2.8 in. (72.0 mm)		
Displacement	151 cu. in. (2.5 liter)		
Compression ratio	11.0:1	Hamann ECU Reprogram Power increase up to 220 hp / 162 kW at 6400 rpm	Hamann ECU Reprogram Power increase up to 237 hp / 174 kW at 6400 rpm
<b>Horsepower (SAE Net)</b>	<b>201 hp (150 kW) @ 6000 rpm</b>	220 HP at 6400 Rev. per min	228 HP at 6400 Rev. per min
<b>Maximum torque (ft. lb.)</b>	<b>181 ft. lbs. (245 Nm) @ 4500 rpm</b>	Max. torque 280 Nm at 4500 rpm	Max. torque 290 Nm at 4750 rpm
<b>Maximum RPM</b>	<b>6700</b>		
Gear Ratios (manual)			
1st	3.50:1	3.50:1	3.50:1
<b>2nd</b>	<b>2.12:1</b>	<b>2.12:1</b>	<b>2.12:1</b>
3rd	1.43:1	1.43:1	1.43:1
4th	1.03:1	1.09:1	1.09:1
5th	0.79:1	0.84:1	0.84:1
Reverse	3.44:1	3.44:1	3.44:1
<b>Final Drive</b>	<b>3.89:1</b>	<b>3.56:1</b>	<b>3.56:1</b>
Dimensions			
Wheelbase	95.2 in. (2415 mm)		
Track Front (standard)	57.7 in. (1465 mm)		
Track Rear (standard)	60.2 in. (1528 mm)		
Track Front (optional)	57.3 in. (1455 mm)		
Track Rear (optional)	59.4 in. (1508 mm)		
Overall length	171.0 in. (4340 mm)		
Overall width	70.1 in. (1780 mm)		
Height (unladen)	50.8 in. (1290 mm)		
Ground clearance (laden)	4.1 in. (105 mm)		
Curb weight (manual)	2822 lbs. (1280 kg)		

202 at 4750. I'm guessing at this one by backing into the torque at HP peak and looking at the difference

Max. torque 295 Nm at 4700 rpm