

GT4 MR Set-Up advice

28.03.19

Pirelli

Fuel	35 kg	vehicle weight [kg]	
Driver weight	75 kg		
Tyre	Slick		

Tyres [bar]	FA left	2,00		FA right	2,00	
	RA left	2,00		RA right	2,00	

1psi 0,0689 bar
max 1,93 bar or 28 psi

Aero Spec.	Front Diffusor				open
	RW GT4	Gurney	5 mm	Pos.	3

Spoiler lip	GT4				
		Target	Actual	Target	Actual

Height measuring wheel [mm]	FA left			FA right		
	RA left			RA right		

Height-Slick 2bar [mm]	FA left	88	Ref. Point (Screw)	FA right	88	Ref. Point (Screw)
	RA left	105	Ref. Point	RA right	105	Ref. Point

Reference see Porsche Cayman GT4 Clubsport Technical Handbook

Antirollbar	FA Blade -GT4 CS MR	3	soft 1	3	stiff 3
	RA Blade -GT4 CS MR	3	soft 1	3	stiff 7

Camber [deg min]	FA left	-3°30'		FA right	-3°30'	
	RA left	-3°00'		RA right	-3°00'	

Check Clearance of trailing arm to chassis!

Toe [min]	FA left	-07'	-1mm	FA right	-07'	-1mm
	RA left	+ 22'	+3mm	RA right	+ 22'	+3mm

Brake balance balance bar Cup (adjustable)

Spring	FA Main	130-140		FA - Help		10/60/80
	RA Main	130-170		RA - Help		10/60/80

Wheelbase [mm]		Target	Actual		Target	Actual
	left	2476		right	2476	

Damper	FA	KW 2way	HspB--Re:	9--7	30mm RD60
	RA	KW 2way	HspB--Re:	10--9	4mm P; 15mm R; 20mm RD60

KW 3way	LsB-HsB-Re	5--9 / 7
KW 3way	LsB-HsB-Re	4--10 / 9

KW FIX
KW FIX

Tyres (Slick)	FA	265/645-18	Pirelli
	RA	305/680-18	Pirelli

(Rain)	FA	265/645-18	Pirelli
	RA	305/680-18	Pirelli

Rims	FA	9"x18"	BBS	RA	10,35"x18"	BBS
-------------	----	--------	-----	----	------------	-----