

Typical Properties

Mobil Delvac Synthetic Gear Oil	75W-90	80W-140
SAE Grade	75W-90	80W-140
Viscosity, ASTM D 445		
cSt @ 40°C	120	310
cSt @ 100°C	15.9	31.2
Viscosity Index, ASTM D 2270	140	139
Pour Point, °C, ASTM D 97	-48	-36
Flash Point, °C, ASTM D 92	205	210
Density @ 15°C kg/l, ASTM D 4052	0.859	0.870

Precautions

Mobil Delvac Synthetic Gear Oil 75W-90 and 80W-140 are manufactured from high quality synthetic base oil, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Special care is also recommended in handling used motor oils. A Service Data Sheet entitled "Safe Handling of Used Motor Oils" is available on request from you Imperial Oil Representative. Please refer to our Imperial Oil Material Safety Data Sheet for further information.

Note: This product is not controlled under Canadian WHMIS legislation.

The Mobil logotype, the Pegasus design, Mobilube and SHC are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

1-2006

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialities, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil
® The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.
™ Trademark of Exxon Mobil Corporation, Imperial Oil, Licensee.

