

BEHE

PERFORMANCE



Run Comment:

Vehicle Specification
 Wheel Diameter (mm): 600.0
 Weight (Kg): 1400.00
 Drive Ratio: 4.22000000
 Trans.C. Factor: 1.000000
 Gearbox: MANUAL
 Gear: 4
 Control Mode: CUSTOM

Vehicle Folder: Hassett 996
 Date: 21-Jul-2015
 Time: 13:18:10
 Run ID: Test 5
 Run No: 1

Correction Method: SAE

AWR

EngRPM	Torque lbft	AxlePow HP	Lambda	AFR	Temp ° F	Baro InHg	RelHum %	Speed Mph
3400	256.973	166.354	0.85	12.49	91.8	29.714	59.23	56.62
3401	256.887	166.356	0.85	12.48	91.7	29.714	59.23	56.64
3500	256.406	170.869	0.88	12.88	91.7	29.714	59.22	58.29
3600	268.807	184.251	0.87	12.74	91.5	29.714	59.19	59.95
3700	287.437	202.493	0.86	12.68	91.5	29.715	59.21	61.62
3800	293.473	212.326	0.87	12.79	91.2	29.715	59.22	63.28
3900	300.154	222.882	0.89	13.09	91.6	29.715	59.24	64.95
4000	307.139	233.917	0.90	13.27	91.7	29.715	59.26	66.61
4100	311.415	243.074	0.90	13.20	91.7	29.716	59.21	68.27
4200	314.076	251.160	0.89	13.08	91.4	29.716	59.19	69.94
4300	314.703	257.654	0.89	13.05	91.4	29.716	59.21	71.61
4400	316.498	265.149	0.88	12.95	91.5	29.717	59.23	73.27
4500	317.232	271.804	0.86	12.61	91.6	29.716	59.23	74.94
4600	315.188	276.054	0.84	12.31	91.4	29.717	59.20	76.60
4700	312.674	279.805	0.83	12.17	91.7	29.717	59.21	78.27
4800	311.014	284.242	0.81	11.97	91.7	29.717	59.24	79.93
4900	312.443	291.496	0.81	11.97	91.8	29.718	59.22	81.60
5000	312.615	297.610	0.81	11.95	92.0	29.717	59.23	83.26
5100	311.478	302.457	0.82	12.12	91.9	29.717	59.24	84.93
5200	308.987	305.922	0.82	12.01	91.9	29.718	59.24	86.60
5300	306.079	308.870	0.83	12.22	91.4	29.718	59.31	88.26
5400	301.388	309.844	0.83	12.17	91.3	29.718	59.24	89.93
5500	300.848	315.047	0.81	11.91	91.8	29.718	59.24	91.59
5600	294.311	313.806	0.79	11.60	91.6	29.718	59.28	93.26
5700	284.348	308.597	0.77	11.29	91.6	29.718	59.25	94.92
5800	277.342	306.274	0.78	11.41	91.6	29.717	59.25	96.59
5900	279.408	313.875	0.79	11.66	91.4	29.717	59.24	98.25
6000	281.217	321.262	0.81	11.88	91.5	29.718	59.21	99.92
6100	278.423	323.371	0.81	11.97	91.6	29.718	59.18	101.58
6200	276.380	326.260	0.82	12.01	91.8	29.718	59.21	103.25
6300	275.055	329.921	0.83	12.17	92.1	29.718	59.25	104.91
6400	269.609	328.534	0.82	12.11	91.8	29.718	59.21	106.58
6500	265.739	328.878	0.83	12.21	91.7	29.718	59.21	108.24
6600	263.675	331.345	0.83	12.20	91.5	29.718	59.24	109.91
6700	260.281	332.035	0.83	12.26	91.8	29.718	59.24	111.57
6800	256.193	331.698	0.83	12.25	91.6	29.718	59.24	113.24
6900	251.358	330.224	0.85	12.54	91.6	29.718	59.28	114.91
7000	249.288	332.250	0.86	12.65	91.5	29.717	59.24	116.57