

# BEHE PERFORMANCE



Run Comment:

Vehicle Specification  
 Wheel Diameter (mm): 600.0  
 Weight (Kg): 1400.00  
 Drive Ratio: 4.22000000  
 Trans.C. Factor: 1.000000  
 Gearbox: MANUAL  
 Gear: 4  
 Control Mode: CUSTOM

Vehicle Folder: Hassett 996  
 Date: 21-Jul-2015  
 Time: 13:14:54  
 Run ID: Test 4  
 Run No: 6

Correction Method: SAE

*FINR*

EngRPM	Torque lbft	AxlePow HP	Lambda	AFR	Temp °F	Baro InHg	RelRun %	Speed Mph
3407	260.689	169.112	0.87	12.81	91.7	29.720	59.44	56.74
3500	257.507	171.602	0.87	12.81	91.8	29.720	59.48	58.29
3600	271.074	185.804	0.87	12.84	91.8	29.720	59.95	59.95
3700	288.101	202.961	0.86	12.62	91.8	29.720	59.59	61.62
3800	296.702	214.670	0.87	12.84	91.9	29.720	59.55	63.28
3900	302.756	224.814	0.89	13.09	91.8	29.719	59.57	64.95
4000	308.154	234.690	0.90	13.26	92.0	29.719	59.51	66.61
4100	309.520	241.624	0.90	13.28	91.8	29.719	59.54	68.28
4200	312.133	249.606	0.90	13.20	91.7	29.719	59.53	69.94
4300	315.635	258.417	0.89	13.01	91.7	29.718	59.42	71.61
4400	316.362	265.035	0.87	12.85	91.8	29.718	59.42	73.27
4500	314.758	269.691	0.86	12.66	91.8	29.718	59.41	74.94
4600	315.336	276.184	0.84	12.35	91.8	29.718	59.42	76.60
4700	313.272	280.341	0.83	12.17	91.4	29.718	59.44	78.27
4800	310.468	283.742	0.83	12.17	91.1	29.718	59.38	79.93
4900	310.273	289.472	0.84	12.30	91.6	29.718	59.51	81.60
5000	311.048	296.117	0.84	12.34	92.0	29.717	59.52	83.26
5100	311.104	302.094	0.83	12.22	92.1	29.717	59.42	84.93
5200	308.791	305.727	0.83	12.27	92.1	29.718	59.36	86.60
5300	303.663	306.432	0.83	12.16	91.3	29.718	59.37	88.26
5400	299.048	307.469	0.83	12.22	91.0	29.719	59.35	89.93
5500	298.607	312.701	0.83	12.15	91.1	29.718	59.26	91.59
5600	292.886	312.286	0.81	11.90	91.0	29.718	59.33	93.26
5700	281.468	305.472	0.79	11.58	91.1	29.718	59.37	94.92
5800	276.179	304.989	0.79	11.56	91.4	29.718	59.40	96.59
5900	277.758	312.022	0.80	11.78	91.7	29.718	59.43	98.25
6000	281.546	321.638	0.81	11.93	92.0	29.718	59.50	99.92
6100	278.924	323.954	0.83	12.16	91.7	29.718	59.47	101.58
6200	272.889	322.139	0.83	12.24	91.1	29.718	59.33	103.25
6300	270.309	324.240	0.83	12.19	91.1	29.718	59.24	104.91
6400	269.945	328.944	0.83	12.19	91.5	29.718	59.38	106.58
6500	266.304	329.577	0.83	12.20	92.1	29.717	59.49	108.24
6600	266.257	334.588	0.83	12.24	92.4	29.718	59.49	109.91